

Bluetooth Cordless Hand Scanner (CHS) Series 7

1D MODELS

Lightweight, Pocket-sized, Dependable



The Socket *Bluetooth* Cordless Hand Scanner (CHS) Series 7 brings industrial-class barcode scanning into a portable, pocket-sized form factor.

Designed for Mobility:

- Small, light, portable
- Wireless with long-range Bluetooth connection
- Excellent ergonomics ensure comfortable use over extended periods
- Dependable performance with long battery life
- Easy integration with applications on diverse mobile computing platforms

General Purpose	7Ci CX2870-1409	Made for		
	7M CX2860-1296	 For intensive scanning throughout an entire work shift. Class 2 laser allows for precise targeting of small barcodes or barcodes in tight spaces, or long-range scanning in hard-to-reach areas like high shelves Great for indoor scanning of ISBN or VIN (even scans through windshields) 		
Durable	7Di CX2877-1472	Made for		
	7P CX2862-1298	- Efficiently scans thousands of barcodes per day, even on reflective surfaces - Best option for scanning VIN indoors and outdoors - even through windshield - High-performance Class 2 laser can read small or poorly printed barcodes - Extra durable for outdoor use, or demanding operations		
Durable Antimicrobial	7DiRx CX2879-1474	Made for Plond PiPad - Same scanner performance as 7Ci - Ideal for healthcare applications like medication administration, charting - Made with antimicrobial materials for healthcare - Extra durable for demanding operations		

HARDWARE FEATURES

- Works with *Bluetooth* enabled PDAs, smartphones, tablets, notebooks and desktop computers:
- Apple iPod touch, iPhone, iPad and Mac OS°
- Android OS
- Windows Mobile, 8, 7, Vista, XP
- BlackBerry OS, QNX
- Class 1 *Bluetooth* 2.1 + EDR provides secure, longrange wireless connection up to 330 ft (100 m)
- Battery Friendly* technology enables extensive battery life on a single charge
- Apple certified CHS 7Ci, 7Di and 7DiRx support Bluetooth SPP connections with iPad, iPhone, iPod touch (Requires SDK or compatible app developed with SDK)¹
- CHS 7Di, 7DiRx and 7P feature extra durable exterior casing to withstand multiple 6.6 ft (2 m) drops to concrete
- Easy to use with automatic reconnections
- LED and beeps indicate good scan, connection, and power status
- Vibrate mode for good scans, great for noisy environments where beeps are hard to hear (7Ci, 7Di, 7DiRx and 7P)
- Allows access to Apple iOS on-screen keyboard
- Supports *Bluetooth* HID connections for easy setup with no software installation²
- Supports Bluetooth SPP connections for advanced scanner control³

SOFTWARE FEATURES (SPP mode only)

- SocketScan[™] 10 keyboard wedge software enters scanned data into any application — no custom programming needed
- Socket EZ Pair automates Bluetooth setup for maximum ease of use
- Suffix support option to automatically add a carriage return or tab after each scan of data
- \bullet Configure beep, LED and vibrate settings
- Enable / disable symbology (barcode type)
- · Monitor scanner battery level
- Determine the symbology or length of a barcode
- SocketScan 10 SDK available with optional developer compensation program http://www.socketmobile.com/products/sdk/

¹CHS 7Ci, 7Di and 7DiRx support *Bluetooth* SPP connections on iOS only with SocketScan 10 SDK v10.0.8 or later or compatible apps developed with the SDK. Find compatible apps at: http://www.socketmobile.com/appstore

²HID not supported for BlackBerry OS or iPhone 3G.

³SPP not supported for Mac OS or QNX. SPP supported for iOS only with CHS 7Ci, 7Di and 7DiRx and SocketScan 10 SDK version 10.0.8 or later or a compatible apps developed with the SDK.

CHS Model	7Ci	7Di	7DiRx	7M	7P			
Scanner SKU #	CX2870-1409	CX2877-1472	CX2879-1474	CX2860-1296	CX2862-1298			
SocketScan 10 SDK	Subscribe to Developer Program to download, SKU# SW1250-1463 (available only from SocketStore.com)							
Dimensions	5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)	5.2 x 1.77 x 1.49 in. (132 x 45.1 x 37.9 mm)		5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)	5.2 x 1.77 x 1.49 in. (132 x 45.1 x 37.9 mm)			
Total Mass	1.6 oz (45 g)	approx. 2.4 oz (68 g)		1.8 oz (51 g)	approx. 2.4 oz (68 g)			
Type of Exterior Case	Standard exterior case with- stands 4 ft (1.2 m) drops to vinyl-covered concrete	Durable, withstands 6.6 ft (2	m) drops to concrete	Standard exterior case with- stands 4 ft (1.2 m) drops to vinyl-covered concrete	Durable, withstands 6.6 ft (2 m) drops to concrete			
Antimicrobial Rating (JIS Z2801:2000 Test) Biosafe HM4100, EPA# 83019-1	N/A	N/A	2.49 on MRSA 6.07 if cleaned with Sani- Cloth Plus cloth wipes	N/A	N/A			
Optional Stylus Tip	Coming soon!			Included, designed for Pocket PC or other resistive device touch screens				
Temperature	Operating: +32 to +122°F (0 to +50°C) Storage: -22 to +158°F (-30 to +70°C) Ranges may vary with battery shelf life.							
Relative Humidity	5% to 95% non-condensing							
Ambient Light	Sunlight: 0 - 110,000 lux			Sunlight: 100,000 lux Artificial light: 4,844 lux				
Battery Type	Two AAA NiMH rechargeable batteries							
Battery Life	19 hours or 11,000 scans ¹		19 hours or 15,000 scans ¹					
Battery Charging Time	· ·	ours (under conditions of 0 to	With AC adapter: approx. 5 hours (under conditions of 0 to +40°C)					
Barcode Scanner Performance								
Scanner Type	Imager (1D)			Class 2 laser (1D)				
Scans Barcodes on Device Screens	✓	✓	✓					
Scans VIN through windshield				✓	✓			
Vibrate Mode for Good Scans	√	√	√		√			
Symbologies Decoded	Same as 7M/P plus: UPC/EAN Inverse 1D, ISBT concatenation	/JAN supplemental redundand ons, Matrix 2 of 5	Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN					
Scan Repetition Rate	50 scans/sec		100 scans/sec bi-directional					
Optical Resolution	5 mil minimum		0.004 inch (0.102 mm) min./barcode element width					
Print Contrast	Minimum 20%		Minimum 25% MRD at 650 nm					
Scan Angle	53.3° ± 3°			Wide (default): 47° ±3° Narrow: 35° ±3°				
Decode Distance ²	5.7 to 50.8 cm (2.25 to 20 in.)		3.8 to 114+ cm (1.5 to 45+ inches)					
Bluetooth Profile Support	Human Interface Device (HID) and Serial Port Profile (SPP) Some OS versions or device models support only one profile.							
Bluetooth Protocol	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption, Bluetooth QD ID B0164000							
Bluetooth Frequency	2.4 to 2.4835 GHz ISM band, supports Advanced Frequency Hopping							
Radio Range	Class 1 Bluetooth: Up to 100 m (330 ft), depending on environment							
OS Support	Please use online compatibility checker for specific device models, OS versions, etc. http://www.socketmobile.com/compatibilitychecker/							
• iOS: iPad, iPhone, iPod touch	√	√	√	√	✓			
• Mac OS	√	√ ·	✓	√ ·	√ ·			
• Android OS	✓	✓	✓	✓	✓			
BlackBerry OS	✓	✓	✓	✓	✓			
• Windows 8, 7, Vista, XP, Embedded Handheld, Mobile	√	√	✓	√	√			
• QNX	✓	✓	✓	√	✓			
Apple iOS certified for iPad, iPhone, iPod touch	Certified. Has authentication	chip to support <i>Bluetooth</i> SPP	N/A - Works only in <i>Bluetooth</i> HID mode with Apple iOS					
SocketScan™ 10 Software	Keyboard wedge for Android, BlackBerry, Windows included. SDK available separately http://www.socketmobile.com/products/sdk/							
Included Items	CHS barcode scanner, AAA rechargeable batteries (2), USB AC charger kit, Lanyard/belt clip with retractable tether, Software							
Warranty	Scanner: One year Accessories: 90 days							
SocketCare Extended Warranty	Sold separately. SocketCare Plus 2 Year - SKU# SC1804-1349 SocketCare Plus 3 Year - SKU# SC1805-1350 http://www.socketcare.com/							
Electrical Safety	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2							
Environmental	RoHS							
EMI / RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC ³							
	ending on vibrate settings and work environment							

¹Battery performance may vary depending on vibrate settings and work environment.

socket* Worldwide Toll-Free

sales@socketmobile.com

+1-510-933-3000 +1-800-552-3300 (USA/Canada) **EMEA** +32 479 49 64 54 UK +44 7787 112109 Asia Pacific +1 510 933 3122 Latin America +1 510 933 3153

²Depends on symbol size, symbology, label media, W-N ratio, scan angle.
³7Di/7DiRx not available in Japan.